



Flexible flashing tape over flashing upstand

2.8x50mm hot dipped galvanised clout nails in to framing. Staggered @ 300 centers. (SS for Exposure Zone D)

Single castellated timber batten *See note

Cavity closer as per E2/AS1 (By others)

Nu-Wall Fascia - can match wall cladding

NC134P
Pre-slotted base channel. Providing 2000mm² of ventilation per linear meter

Optional cavity closure:
Use standard 15mm head flashing see NW-VOC-031

Soffit by others

NC138 + NC139
Termination flashing base and cap.

NC226
Impervious barrier between batten & cladding

Drained and vented cavity as per E2/AS1

NC203E
Fixing bracket @ 600mm centers

NC204
10g ss csk screws with 30mm min embedment

NC226
Impervious barrier between batten & cladding

Single castellated timber batten 200mm from underside of top plate or last batten *See note

Interactive assembly instructions available
<http://wksp.nz/nw-voc-sof>



Get WORKINGSPEC from Apple App Store/Google Play

General note:

- Cladding fixings omitted for clarity

Cavity batten note:

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required



BRANZ Appraised
Appraisal No. 556 [2019]



Nu-Wall cladding vertical on cavity

Typical Nu-Wall fascia to soffit

NW-VOC-030.01

Drawn by: Nu-Wall

Date: 14/03/2022

Checked by: RL, GT

Scale: 1:2 @ A4

© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited